


1. 70 (for 1 Glamping) + 40 (for each terrace) concrete paving slabs 50 x 50 x 5 cm (1'-8" x 1'-8" x 0'-2") min 63 lb each, or 252 lb for 4 slabs, normally available in any hardware store
must be purchased by the customer and will be assembled by the assembly team

2. Compacted gravel mixture 4/32, horizontal, 36 m² (388 ft²), layer height = at least 5 cm (2").
Gravel mixture is optional - but recommended (otherwise there is a risk of settlement and moisture on the foundation and increased assembly work due to unevenness)
Apply the gravel mixture to the subsoil and level (no excavation necessary)

3. Power connection, 2x220 V (CEE plug 7/4) 16 A
--> must be laid by the customer to the location according to the drawing



4. Forklift suitable for the terrain
Load capacity = 2 t (2.2 US Ton), min. lifting height = 4.2 m (13'-10")
-> must be provided by the customer before the start of assembly
-> alternatively: Unloading of individual parts by hand with 4 people possible, is to be taken over by the customer

5. Access possibility for articulated lorries directly to the site.
Length = 18.70 m (61'-5"), height = 4 m (13'-2"), width = 2.55 m (8'-5")
-> alternatively: unloading of individual parts by hand with 4 people possible, is to be taken over by the customer

6. Unobstructed area for assembly directly at the installation site of ca. 40 ft x 20 ft (see dashed line in drawing)



Glamping COMFORT AMBIENCE

Strong*/Extend*

Scale:	1:50 A3
Date:	21.12.2023
Weight with paving slabs:	5680 kg (6,26 US ton)
Weight without paving slabs:	1360 kg (1,50 US ton)
Packing size:	5,8 m x 1,2 m x 1 m (19'-1" x 4'-0" x 3'-4")



FURTHER INFORMATION AND CONDITIONS:

- The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4% . They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.
- If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.
- To avoid dampness, the space underneath the construction must be kept free of plants or similar objects. 20cm (8") of ventilation under the wooden construction must always be guaranteed.
- The construction is calculated for a snow load of 20 kg/m² (4 lbs / m²) and wind speeds of up to 100 km/h (92 fts / s). The Strong version is calculated for a snow load of up to 200 (40 lbs / m²).
- In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner.
Make sure not to damage the surface coating (no high-pressure cleaner, etc.)