





Pavillon 2 Connect
STRONG
PRO / COMFORT*

STROHBOLD

Scale: 1:100 | A3

Date: 05.04.2023

Weight with paving slabs: 15830 kg (17,45 US ton)
16150 kg (17,80 US ton)

Weight without paving slabs: 6730 kg (7,42 US ton)
7050 kg (7,77 US ton)

Packing size: 13 m x 2,2 m x 2,5 m
(42'-8" x 7'-3" x 8'-2")



- FURTHER INFORMATION AND CONDITIONS:
- 8. The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4%. They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.
 - 9. If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.
 - 10. To avoid dampness, the space underneath the construction must be kept free of plants or similar objects. 20 cm of ventilation under the wooden construction must always be guaranteed.
 - 11. The construction is calculated for a snow load of 200 kg/m² (40 lb / ft²) and wind speeds of up to 160 km/h (145 ft / s).
 - 12. In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner. Make sure not to damage the surface coating (no high-pressure cleaner, etc.)