1. The dashed area in the subsoil must be kept free for groudn anchors. It must be possible to drive the soil nails into the ground to a minimum depth of 90 cm (3 ft). No liability will be accepted for any possible damage (power lines, etc.).
-> In the case of rocky ground, the customer must commission a company to pre-drill the drive-in holes with appropriate equipment.

2. Forklift suitable for the terrain
Load capacity = 2 t (2.2 US ton), min. lifting
height = 4.2 m (13'-10").
-> Must be provided by the customer before the start of assembly.

3. Access possibility for articulated lorries directly to the site.
Length = 18.7 m (61'-5"), height = 4 m (13'-2"), width = 2.55 m (8'-5").
-> alternatively: material can be lifted to the site with a crane (to be provided and paid by the customer).

4. Unobstructed area for assembly directly at the installation site of ca. 15 x 25 m (50 ft x 85 ft).
(for precise information, see dashed line in drawing)

STROHBOID

Pavillon 2 Connect BASIC

1:100 I A3

13.03.2023

2070 kg (2,3 US ton)

13 m x 2,2 m x 2,5 m
(42'-8" x 7'-3" x 8'-5")

FURTHER INFORMATION AND CONDITIONS:

5. The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4% . They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.

6. If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.

7. The construction is calculated for a snow load of 20 kg/m² (4 lb / ft²) and wind speeds of up to 100 km/h (91 ft / s). For an (additional fee), constructive snow load reinforcements of up to 200 kg/m² (40 lb / ft²) and foundations designed for higher wind speeds are available for all products.

8. In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner.
Make sure not to damage the surface coating (no high-pressure cleaner, etc.)

Datei: US _ STROHBOID Pavillon 2 Connect BASIC 160 m² _ product plan A3

0 mm 100 mm