1. The dashed area in the subsoil must be kept free for ground anchors. It must be possible to drive the soil nails into the ground to a minimum depth of 90 cm. No liability will be accepted for any possible damage (power lines, etc.).
-> In the case of rocky ground, the customer must commission a company to pre-drill the drive-in holes with appropriate equipment.

2. Forklift suitable for the terrain
Load capacity = 2 t, min. lifting height = 4.2 m
alternatively: Unloading of individual parts by hand is possible, will be charged additionally

3. Access possibility for articulated lorries directly to the site.
Length = 18.70 m, height = 4 m, width = 2.55 m
alternatively: material can be lifted to the site with a crane (to be provided by the customer)

STROHBOID

# Pavillon 2 Connect BASIC

| | |
|---|---|
| Scale: | 1:100 I A3 |
| Date: | 13.03.2023 |
| Weight: | 2070 kg |
| Packing size: | 13 m x 2,2 m x 2,5 m |

FURTHER INFORMATION AND CONDITIONS:

5. The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4% . They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.

6. If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.

7. The construction is calculated for a snow load of 20 kg/m² and wind speeds of up to 100 km/h. For an (additional fee), constructive snow load reinforcements of up to 200 kg/m² and foundations designed for higher wind speeds are available for all products.

8. In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner.
Make sure not to damage the surface coating (no high-pressure cleaner, etc.)



0 mm 100 mm