2. Only with COMFORT variant: 8 x 1500W Infrarot-Deckenheizstrahler;
Recommendation: Blumfeldt company Hitzkopf. Item number: 10028637.
-> Must be purchased, paid for and provided by customer prior to assembly and will be assembled by assembly team.

1. 268 (incl. 10% reserve) concrete paving slabs 50 x 50 x 5 cm (min. 28.8 kg each), normally available in any hardware store.
-> must be purchased and paid by the customer and will be assembled by the assembly team

3. Compacted gravel mixture 4/32, horizontal, 81 m², layer height = min. 5 cm when compacted (compression min. 15%).
-> Gravel mixture is optional - but recommended (otherwise there is a risk of settlement and moisture on the foundation and increased assembly work due to unevenness)
-> Apply the gravel mixture to the subsoil and level (no excavation necessary).

3. POWER:
Only with COMFORT variant: power connection, 32 A high-voltage current with CEE-form plug.
-> must be laid by the customer to the location according to the drawing

5. Forklift suitable for the terrain
Load capacity = 2 t, min. lifting height = 4.2 m.
Must be provided by the customer before the start of assembly.

6. Access possibility for articulated lorries directly to the site.
Length = 18.70 m, height = 4 m, width = 2.55 m.
-> alternatively: material can be lifted to the site with a crane (to be provided by the customer).

7. Unobstructed area for assembly directly at the installation site of ca. 15 x 15 m
(for precise information,see dashed line in drawing)

*Note: all parts in the comfort version of this product plan are denoted by blue color and are not included in the PRO version.

STROHBOID

Pavillon 70
PRO / COMFORT*

Scale:	1:50 I A3
Date:	23.02.2023
Weight with paving slabs:	9700 kg 9860 kg
Weight without paving slabs:	2680 kg 2840 kg
Packing size:	13 m x 2,2 m x 2,4 m

FURTHER INFORMATION AND CONDITIONS:

8. The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4% . They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.

9. If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.
https://www.tesa.com/en-gb/consumer/tesa-ultra-power-clear-repair-tape.html

10. To avoid dampness, the space underneath the construction must be kept free of plants or similar objects. 20 cm of ventilation under the wooden construction must always be guaranteed.

11. The construction is calculated for a snow load of 20 kg/m² and wind speeds of up to 100 km/h. For an (additional fee), constructive snow load reinforcements of up to 200 kg/m² and foundations designed for higher wind speeds are available for all products.

12. In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner.
Make sure not to damage the surface coating (no high-pressure cleaner, etc.)