





**Pavillon 2 Connect**  
**STRONG**  
**PRO / COMFORT\***

Scale: 1:100 | A3

Date: 05.04.2023

Weight with paving slabs: 15830 kg  
16150 kg

Weight without paving slabs: 6730 kg  
7050 kg

Packing size: 13 m x 2,2 m x 2,5 m



- FURTHER INFORMATION AND CONDITIONS:**
8. The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4% . They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.
9. If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.  
<https://www.tesa.com/en-gb/consumer/tesa-ultra-power-clear-repair-tape.html>
10. To avoid dampness, the space underneath the construction must be kept free of plants or similar objects. 20 cm of ventilation under the wooden construction must always be guaranteed.
11. The construction is calculated for a snow load of 200 kg/m² and wind speeds of up to 160 km/h.
12. In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner.  
Make sure not to damage the surface coating (no high-pressure cleaner, etc.)