


1. 796 concrete paving slabs 50 x 50 x 5 cm (min. 28.8 kg each)
must be purchased and paid by the customer and will be laid
down by the assembly team


2. 32 x 1500W infrared ceiling heater,
Recommendation: Blumfeldt company Hitzkopf
item number: 10028637
--> must be purchased by the customer and will
be assembled by the assembly team

3. Compacted gravel mixture 4/32, horizontal, 372 m² (4004 ft²), layer
height = at least 5 cm (min. 2") when compacted (compression min. 15%).
Gravel mixture is optional - but recommended (otherwise there is a risk
of settlement and moisture on the foundation and increased assembly
work due to unevenness)
Apply the gravel mixture to the subsoil and level (no excavation
necessary)

4. 4 x 32 A high-voltage current with
CEE-form plug
--> must be laid by the customer to the
location according to the drawing (one
for each structure at any corner)



5. Forklift suitable for the terrain.
Load capacity = 2 t (2.2 US ton), min. lifting
height = 4.2 m (13'-10").
-> Must be provided by the customer before the start of
assembly:



6. Access possibility for articulated lorries
directly to the site.
Length = 18.7 m (61'-5"), height = 4 m
(13'-2"), width = 2.55 m (8'-5")
alternatively: material can be lifted to the
site with a crane (to be provided by the
customer).

7. Unobstructed area for
assembly directly at the
installation site of approx. 30 m x
40 m (95 ft x 130 ft)
(for precise information, see
dashed line in drawing)

*All parts in the Comfort version of this product plan
are denoted by blue color and are not included in the PRO
version.