



Glamping COMFORT AMBIENCE Strong*/Extend*

Scale:	1:50 A3
Date:	21.12.2023
Weight with paving slabs:	5680 kg
Weight without paving slabs:	1360 kg
Packing size:	5,8 m x 1,2 m x 1 m



FURTHER INFORMATION AND CONDITIONS:

- The surfaces of the construction are treated with LIGNEA RESEDA exterior wood oil special mixture, depending on the color, either with a mixing ratio of 12% or 4%. They can be re-oiled if necessary. Wooden elements exposed to the weather and the floor are oiled with 12%, the remaining elements with 4%. Wooden elements that are exposed to the weather should be re-oiled annually for longer durability.
- If the translucent membrane is damaged due to excessive mechanical stress (vandalism, hurricane), it can be repaired with Tesa-ultra-power-clear repair tape.
- To avoid dampness, the space underneath the construction must be kept free of plants or similar objects. 20 cm of ventilation under the wooden construction must always be guaranteed.
- The construction is calculated for a snow load of 20 kg/m² and wind speeds of up to 100 km/h. The Strong version is calculated for a snow load of up to 200 kg/m².
- In case the translucent membrane gets dirty, it can be cleaned carefully either with a telescopic brush or/and cloth with water. If heavily stained, clean it with a PVC (membrane) cleaner.
Make sure not to damage the surface coating (no high-pressure cleaner, etc.)